

intAct Gel-Power

Supply batteries
Sealed block batteries | Gel technology



intAct
Battery-Power

intAct Gel-Power

Supply batteries
Sealed block batteries | Gel technology

The intAct gel-power delivers secure a maximum supply energy for high cyclical stress in professional applications. It is ideal as a buffer for irregular charging and discharging processes such as, for example, with solar-powered applications.

Thanks to the higher lifespan compared to traditional batteries, the intAct gel-power is also efficient from an economical point of view.

The robust construction combined with the specific benefits of the gel technology makes the intAct gel-power highly shock resistant.

Battery	Volt	Capacity	Length mm	Width mm	Height mm	Position of terminal	Terminal
GEL-16	12	14 AH (c5), 16 AH (c20), 18 AH (c100)	181	76	167	0	G
GEL-19	12	17 AH (c5), 19 AH (c20), 21 AH (c100)	185	80	170	0	G
GEL-25	12	22 AH (c5), 25 AH (c20), 27 AH (c100)	167	176	126	0	G-M5
GEL-30	12	25 AH (c5), 30 AH (c20), 32 AH (c100)	197	132	180	1	G-M6
GEL-40B	12	33 AH (c5), 40 AH (c20), 41 AH (c100)	210	175	175	0	A
GEL-50B	12	40 AH (c5), 50 AH (c20), 55 AH (c100)	246	175	190	0	A
GEL-50MK	12	43 AH (c5), 50 AH (c20) 55 AH (c100)	238	140	235	0	A
GEL-55	12	44 AH (c5), 55 AH (c20), 60 AH (c100)	261	135	230	0	A
GEL-60	12	51 AH (c5), 60 AH (c20), 65 AH (c100)	278	175	190	0	A
GEL-60B	12	51 AH (c5), 60 AH (c20), 65 AH (c100)	278	175	190	0	A
GEL-60MK	12	47,4 AH (c5), 60 AH (c20), 70 AH (c100)	259	166	178	0	F-M6
GEL-75	12	63 AH (c5), 75 AH (c20), 80 AH (c100)	260	171	210	1	F-M6
GEL-80B	12	65 AH (c5), 80 AH (c20), 85 AH (c100)	353	175	190	0	A
GEL-85	12	72 AH (c5), 85 AH (c20), 90 AH (c100)	330	171	236	1	A
GEL-115	12	94 AH (c5), 115 AH (c20), 130 AH (c100)	286	269	230	2	A
GEL-120	12	90 AH (c5), 120 AH (c20), 135 AH (c100)	513	189	223	3	A
GEL-125	12	105 AH (c5), 125 AH (c20), 140 AH (c100)	345	175	290	0	A
GEL-140	12	120 AH (c5), 140 AH (c20), 155 AH (c100)	513	223	223	3	A
GEL-210	12	160 AH (c5), 210 AH (c20), 230 AH (c100)	518	276	242	3	A
GEL-180-06V1	6	160 AH (c5), 180 AH (c20), 200 AH (c100)	244	190	275	1	A
GEL-180-06V2	6	160 AH (c5), 180 AH (c20), 200 AH (c100)	261	181	269	0	A
GEL-200-06	6	180 AH (c5), 200 AH (c20), 230 AH (c100)	244	190	275	1	A
GEL-300-06	6	240 AH (c5), 300 AH (c20), 330 AH (c100)	312	180	359	1	A
A504/3.5S	4	3,5 AH (c20)	90	34	64		Fast-on
A506/3.5S	6	3,5 AH (c20)	134	34	64		Fast-on

Product line: intAct Gel-Power, gel batteries 12 V + 6 V + 4 V
Model: Gel technology – grid plates – sealed – completely maintenance-free
Status: GUG = filled and charged
Quality: OEM quality
Storage life: Storage life of up to 12 months
Number of cycles: 500 cycles according to IEC 254-1
Cover strip: Model = B

Type of terminal: A = cone terminal according to DIN EN 60 095 T2
 G = threaded connector – drilled flat contact
 F = threaded connector – internal thread
Properties: Low self-discharge, completely maintenance free
Use: Passenger cars – trucks – agricultural machinery – tractors – buses – construction equipment – car audio – recreational and sports vehicles – sail boats – motor yachts – electric boats – US cars