



FHK 50 12-24V



FHK 85 12-24V



FHF 50 12-24V



FHF 85 12-24V



FHK 85 - glass shelves



FHF 85 - baskets



FHC 85 - built-in freezer



Coolers and freezers

FHK
FHF
FHC

- Reversible door
- Internal light - only FHK 85 and FHC 85
- Low voltage protection

Model	FHK 50 12-24V	FHF 50 12-24V	FHK 85 12-24V	FHF 85 12-24V	FHC 85 12-24V
Connection power (volt)	12/24 DC	12/24 DC	12/24 DC	12/24 DC	12/24 DC
Volume - cooling/freezing (litres)	50 / -	- / 34	128 / -	- / 88	103 / 15
External dim. (WxDxH / mm)	440×470×510	440×470×510	550×576×845	550×576×845	550×576×845
Temp. area (°C)	+3 - +10	÷18	+3 - +10	÷18	+3 - +10 / ÷10
Nominal power (watt)	48	48	48	65	65
Absorption power (Kw/24t)*	0,29	0,62	0,34	0,86	0,86
Nominal absorption (A/24t)*	12V:24,0/24V:12,0	12V:51,0 / /24V:25,5	12V:28,0/24V:14,0	12V:72,0/24V:36,0	12V:72,0/24V:36,0
Weight (kg)	17	18	28	30	30

Varenummer **FHK 50 12-24V** **FHF 50 12-24V** **FHK 85 12-24V** **FHF 85 12-24V** **FHC 85 12-24V**

* Supplied data have been taken at an ambient temperature of 32°C and an internal temperature of temp. på 5-7°C